## Lamp Selection Guide



		INCAND	SCENT TYPE			
Size T-1 Sub-midget	LAMP NO.	RATED VOLTAGE	AMPERAGE	APPROX. CANDLEPOWER	AVERAGE LIFE (Hrs.)	NOTES
Flange Base	682	5.0	.060	.03	100,000	MS24515-682
	685	5.0	.060	.05	100,000	MS24515-685
A	718	5.0	.115	.15	40,000	MS24515-718
Group M	6839	28.0	.024	.13	16,000	MS3338-6839
	331	1.35	.06	.01	500	
	268	2.5	.35	.21	10,000	
	338	2.7	.06	.04	6,000	MS25237-338
	345	6.0	.04	.03	10,000	
Size T-1 <sup>3</sup> 4	328	6.0	.20	.34 @ 5 V	1,000	MS25237-328
Midget	380	6.3	.04	.02	50,000	
Flange Base	350	6.3	.15	.45	3,000	
	349	6.3	.20	.55	3,000	
	381	6.3	.20	.40	50,000	
Group A	344	10.0	.014	.004	10,000	
	367X	10.0	.04	.08	5,000	
	330	14.0	.08	.50	750	MS25237-330
	370	18.0	.04	.15	1,000	
	327	28.0	.04	.34	1,000	MS25237-327
	387	28.0	.04	.30	25,000	MS25237-387
	316	6.0	.70	3.4	500	MS25231-316
Size T-3 <sup>1</sup> ⁄4	44	6.3	.25	.9	3,000	
Miniature Bayonet Base	47	6.3	.15	.52	3,000	
Single Contact	1816	13.0	.33	3.0	1,000	
	1815	14.0	.20	1.4	3,000	
	313	28.0	.17	3.0	500	MS25231-313
	1819	28.0	.04	.34	1,000	MS25231-181
	1829	28.0	.075	1.0	1,000	MS25231-182
Group B	1835	55.0	.05	1.1	10,000	
		NEON	GLOW TYPE			
Size T-2	LAMP NO.	RATED VOLTAGE	STAR VOLT		MMENDED RESISTOR	NOTES
	AIG	105-125 AC OR DC		/AC /DC 68KΩ		
Group C	A1H (High Brightness)	105-120 VAC 150 VDC	95 \	/AC	27KΩ	
Size T-2	C7A	105-125 AC OR DC		/AC /DC	68KΩ	MS25252-C7A
Group D	C9A (High Brightness)	105-125 AC OR DC	105 \	105 VAC		MS25252-C9A
		AMPS WITH	BUILT-IN RES	SISTOR		
Size T-2	LAMP NO.	RATED STA VOLTAGE VOL		NG GE	NOTES	
	A1HR1	105-125 VAC	65 VA 95 VD	C		
-	A1GR1	105-125 VAC	95 VA	95 VAC		
	A1GR2	105-125 VAC	130 VA	c		

**INDICATOR** 

LIGHTS

## Notes:

1. Candlepower values indicated are approximate initial mean spherical candlepower at rated voltage.

2. Service conditions such as voltage surges, temperature, shock, and vibration may contribute to a shorter average life.